

Grease AF-2 NLGI 2 400-001 EP-multipurpose lithium-based grease

GREASE 400-001 is natural colored lithium based EP Multipurpose grease with distinct high pressure additivation. **GREASE 400-001** is also additivated with components for an increasing oxidation stability and corrosion protection.

GREASE 400-001 is for applications like roller bearings with high and temporary jerky compressive load and vibrations at normal and increasing temperatures. Based on the smooth texture is **GREASE 400-001** excellent pumpable in all kinds of central lubrication systems and ensured also the application in machines with increasing requirements.

Characteristics:

- provides protections against frictional corrosion and abrasion
- application temperatures from -30°C to +120°C, temporary up to 130°C
- does not contain solid lubricants
- oxidation resistant and stable while penetration
- water resistant and adherent
- good corrosion protection and high ability of pressure absorption

Technical facts:

NLGI grade	2	DIN 51818
Viscosity at +40 °C	190 mm ² /s	DIN EN ISO 3104
Drop point	190 °C	DIN ISO 2176
Stability while penetration	280 till 310	DIN ISO 2137
Water resistance	1 – 90	DIN 51807
Corrosion protection	Grade 0/0	DIN 51802
Copper corrosion	1 – 100	DIN 51811
SKF-running test 120 °C	Passed	DIN 51806
Lubricating grease period of usage at 120 °C	F ₅₀ >150 h	DIN 51821
Soap base	Li-12-Hydroxystearat	DIN 51558

(The stated technical facts are average values.)

Before using please notice the regulations of the manufacturer concerning the characteristics of quality, the environmental temperature and the intervals of oil changes.

Health protection: With the use of lubricants it is necessary to consider the general rules of employment protection. For more information please see the material safety data sheet.

Fritsche-Service: Sales representatives, chemists and engineers are available at any time to state any application technology advices.

05/2014

Erfüllungsort für Lieferung und Zahlung ist Tostedt. Gerichtsstand ist Tostedt. Placement of fulfillment for duties arising from the contract is Tostedt.

FRITSCH GMBH & CO. KG
Eichenhöhe 10
DE - 21255 Kakenstorf

Tel. +49 (0) 4186 888 29 0
Fax +49 (0) 4186 888 29 99
Email: info@fritsche-gmbh.de
www.fritsche-gmbh.de
www.centrallubrication.com

VAT.DE 262.239.982
St.Nr. 15.205.13302
Geschäftsführer/MD
Gerald K. Fritsche
Amtsgericht Tostedt HRB

Bank: Hamburger Sparkasse
IBAN:DE05 200 505 50 1383 1338 06
SWIFT (BIC): HASPDEHH
Konto/Account No. 1383 1338 06
BLZ/Routing No. 200 505 50

